



UDY Corporation
We make analysis practical

Introducing our lowest priced, top of the line, Lab Sample Mill



- USDA recommendation for NIR sample preparation.
- Fine consistent particle size.
- No thermal degradation.
- Powerful 3/4 horse motor.
- Flow thru design.
- Easy cleanup between samples.
- Fast grinding to a consistent particle size.
- **All of the same components as our top of the line model except the drive belt assembly.**
- World famous dependability from UDY Corporation
- Now economically priced.
- Fits all standard accessories.

Cyclone Sample Mill

Now! You can have the best

- **Dimensions** 26x26x47 cm (10.3"x10.3"x18.5")
- **Net weight:** 13 kg (28lb).
- **Shipping weight:** 15 kg (37lb).
- 3/4 hp capacitor start, **synchronous induction motor.**
- Totally enclosed **motor** with cooling fan.
- **Available in 115/230v 50/60 Hz power models.**
- **Impeller speeds:** 12,600 rpm with 60 Hz power or 10,400 rpm with 50 Hz power.
- **Accessories included:** 3 collection bottles w/snap-cap, 2 hex wrenches, antistatic solution, 1.0 and .5 mm screens.

Only from
UDY Corporation

201 Rome Court, Fort Collins CO 80524 USA
Voice (970) 482.2060 Fax: (970) 482.2067
E-mail udy@udycorp.com www.udyone.com

PolyFlex Belt Drive

Model 3010-080P 115v/60Hz

Model 3010-081P 220v/50Hz

